
IPMECD-F-ML-M1515

Folding Arm



- 3 m (9.84 ft) folding arm (1.5 m (4.92 ft)+1.5 m (4.92 ft)) suitable for both side of the barrier gate. Made of aluminum alloy with electrostatic powder coating for rust prevention. Features red/green LED strip lighting and a flexible anti-smash rubber strip at the base.

Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic

Color	Red and white
Matched Product	DHI-IPMECD-206E-XF series barrier

General

Operating Temperature	–35 °C to +65 °C (–31 °F to +149 °F)
Storage Temperature	–35 °C to +65 °C (–31 °F to +149 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Casing Material	Metal (aluminium)
Product Dimensions	3050 mm × 80 mm × 45 mm (120.08" × 3.15" × 1.77") (L × W × H)
Packaging Dimensions	3200 mm × 200 mm × 100 mm (125.98" × 7.87" × 3.94") (L × W × H)
Net Weight	6.6 kg (14.55 lb)
Gross Weight	7.2 kg (15.87 lb)
Installation	Install onto the matching barrier
Anti-corrosion Level	Basic Protection *The products are designed for general use and are applicable even in areas with no specific requirements for anti-corrosion protection.

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-F-ML-M1515	Folding Arm

Dimensions (mm[inch])

